



Darba spiediens
10 bar
Vides temperatūra
Max. +90 °C
Vielas temperatūra
max. +90 °C
Materiāls
Brass with a bare metal surface

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītne 1	Vītne 2	L1 mm	L2 mm	L3 mm	SW
K- 07 40 44 60	R 1/8	R 1/8	21.0	8.0	8.0	10 mm
K- 07 40 44 61	R 1/8	R 1/4	24.5	8.0	11.5	14 mm
K- 07 40 44 62	R 1/8	R 3/8	26.0	8.0	13.0	17 mm
K- 07 40 00 26	R 1/4	R 1/4	30.0	12.0	12.0	14 mm
K- 07 40 44 66	R 1/4	R 3/8	29.5	11.5	13.0	17 mm
K- 07 40 44 67	R 1/4	R 1/2	32.5	11.5	15.5	22 mm
K- 07 40 00 27	R 3/8	R 3/8	38.0	16.0	16.0	22 mm
K- 07 40 44 70	R 3/8	R 1/2	34.0	15.5	13.0	22 mm
K- 07 40 44 71	R 3/8	R 3/4	36.5	13.0	17.5	27 mm
K- 07 40 00 28	R 1/2	R 1/2	38.0	16.0	16.0	27 mm
K- 07 40 44 74	R 1/2	R 3/4	39.0	17.5	15.5	27 mm
K- 07 40 44 75	R 1/2	R 1	42.5	20.0	15.5	34 mm
K- 07 40 00 29	R 3/4	R 3/4	51.5	22.0	22.0	32 mm
K- 07 40 44 78	R 3/4	R 1	44.5	20.0	17.5	34 mm
K- 07 40 00 30	R 1	R 1	47.0	19.5	19.5	41 mm