



Darba spiediens  
10 bar  
Vides temperatūra  
Max. +90 °C  
Vielas temperatūra  
max. +90 °C

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	SW
K- 07 40 34 45	G 1/8	3.5	15 mm
K- 07 40 34 46	G 1/4	3.5	17 mm
K- 07 40 34 47	G 3/8	4.5	19 mm
K- 07 40 34 48	G 1/2	5.0	24 mm
K- 07 40 34 49	G 3/4	5.0	32 mm
K- 07 40 34 50	G 1	6.0	41 mm
K- 07 40 44 33	G 1 1/4	8.5	50 mm
K- 07 40 44 34	G 1 1/2	8.5	60 mm
K- 07 40 44 35	G 2	11.0	70 mm
K- 07 40 34 51	M 10 x 1	4.0	14 mm
K- 07 40 34 52	M 12 x 1	5.0	17 mm
K- 07 40 34 54	M 14 x 1	4.0	19 mm
K- 07 40 34 55	M 16 x 1	5.0	22 mm
K- 07 40 34 56	M 20 x 1.5	4.5	27 mm
K- 07 40 34 57	M 22 x 1	4.5	27 mm
K- 07 40 34 58	M 28 x 1,5	6.0	36 mm