


K-RD NIPPEL LANG 1

Reducing nipples, long type



Darba spiediens
10 bar
Vides temperatūra
Max. +90 °C
Vielas temperatūra
max. +90 °C
Materiāls
Brass with a bare metal surface

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Iekšējā vītne	Ārējā vītne	L1 mm	L2 mm	SW
K- 07 40 00 65	M 5	M 5	15.0	5.0	8 mm
K- 07 40 00 66	G 1/8	M 5	17.0	5.0	14 mm
K- 07 40 00 67	M 5	G 1/8	17.0	7.0	14 mm
K- 07 40 00 64	G 1/4	G 1/8	26.0	10.0	17 mm
K- 07 40 00 70	G 1/8	G 1/4	28.0	10.0	17 mm
K- 07 40 00 71	G 1/4	G 1/4	28.0	10.0	17 mm
K- 07 40 00 68	G 3/8	G 1/4	26.0	10.0	19 mm
K- 07 40 00 72	G 1/4	G 3/8	29.0	10.0	19 mm
K- 07 40 00 73	G 3/8	G 3/8	29.0	10.0	19 mm
K- 07 40 00 69	G 1/2	G 3/8	27.0	12.0	24 mm
K- 07 40 00 74	G 3/8	G 1/2	34.0	12.0	24 mm
K- 07 40 00 75	G 1/2	G 1/2	34.0	12.0	24 mm
K- 07 40 00 76	G 3/4	G 1/2	38.0	13.0	32 mm
K- 07 40 00 77	G 1	G 3/4	26.0	11.0	36 mm