

K-RED STUECK 20-63 INFI

Reducer Ø 20 mm – Ø 63 mm



Darba vides
Compressed air, vacuum, inert gases
Eksploatācijas spiediens
-0,99 bar - 15 bar
Temperatūras diapazons
-20 °C to +80 °C
Blīvgredzens
NBR
Blīvējums
NBR
Drošības gredzens
Technopolymer
Korpuss
Nickel-plated brass
Spīlgredzens
Stainless steel 1.4301
Uzgrieznis
Nickel-plated brass

Produkts

Apzīmējums	Caurules ārējais Ø	B mm	D1 mm	D2 mm	E1 mm	E2 mm	L mm	SW1 mm	SW2 mm
K- 07 40 54 26	25 - 20 mm	31.5	25.0	20	43.5	34.5	48.0	42	30
K- 07 40 54 27	32 - 20 mm	31.5	32.0	20	54.0	34.5	48.5	52	30
K- 07 40 54 28	32 - 25 mm	38.5	32.0	25	54.0	42.5	55.0	63	35
K- 07 40 54 29	40 - 20 mm	31.5	40.0	20	65.0	34.5	50.0	63	30
K- 07 40 54 30	40 - 25 mm	38.5	40.0	25	65.0	42.5	56.5	63	35
K- 07 40 54 31	40 - 32 mm	46.0	40.0	32	65.0	52.0	63.5	63	45
K- 07 40 54 32	50 - 32 mm	46.0	50.0	32	75.0	52.0	63.5	73	45
K- 07 40 54 33	50 - 40 mm	52.0	50.0	40	75.0	63.0	69.0	73	55