



## Darbības princips

Installation of a new connector without opening the pipe system

Uzstādīšanas stāvoklis

horizontally, vertically

Materiāls

Niķelēts misiņš

## Produkts

Apzīmējums	Caurules ārējais Ø	B	D	D1	E	F	L1	L2	L3	L4	SW	SW1
		mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
K- 07 40 54 44	32 - 20 mm	31.5	32	20.0	34.5	34.0	136.5	100.5	78.0	57.0	30	5
K- 07 40 54 45	32 - 25 mm	38.5	32	25.0	42.5	34.0	144.5	108.5	78.0	57.0	35	5
K- 07 40 54 46	40 - 20 mm	31.5	40	20.0	34.5	34.0	148.5	108.0	89.5	64.0	30	5
K- 07 40 54 47	40 - 25 mm	38.5	40	25.0	42.5	34.0	156.5	116.0	89.5	64.0	35	5
K- 07 40 54 48	50 - 20 mm	31.5	50	20.0	34.5	42.5	167.5	118.5	105.5	74.0	30	6
K- 07 40 54 49	50 - 25 mm	38.5	50	25.0	42.5	42.5	175.5	126.5	105.5	74.0	35	6
K- 07 40 54 50	63 - 20 mm	31.5	63	20.0	34.5	42.5	185.0	130.0	119.0	81.0	30	6
K- 07 40 54 51	63 - 25 mm	38.5	63	25.0	42.5	42.5	193.0	138.0	119.0	81.0	35	6