

K-T STECK VB SCHANH 20-63

INFI

T-push-in connector Ø 20 mm – Ø 63 mm with integrated gooseneck

Darba vides
Compressed air, vacuum, inert gases
Eksploatācijas spiediens
-0,99 bar - 15 bar
Temperatūras diapazons
-20 °C to +80 °C
Blīvgredzens
NBR
Blīvējums
NBR
Drošības gredzens
Technopolymer
Korpuss
Nickel-plated brass
Spīlgredzens
Stainless steel 1.4301
Uzgrieznis
Nickel-plated brass



Produkts

Apzīmējums	Caurules ārējais Ø	B1 mm	B2 mm	C1 mm	C2 mm	D1 mm	D2 mm	E1 mm	E2 mm	L1 mm	L2 mm	SW mm	SW1 mm	SW2 mm
K- 07 40 53 92	20 - 20 - 20 mm	31.5	31.5	48.0	22.5	20.0	20	34.5	34.5	109.0	54.0	28	30	30
K- 07 40 53 93	25 - 20 - 25 mm	38.0	31.5	45.5	27.5	25.0	20	42.5	34.5	121.5	59.0	35	35	30
K- 07 40 53 94	32 - 20 - 32 mm	46.0	31.5	54.5	31.5	32.0	20	52.0	34.5	146.5	63.0	45	45	30
K- 07 40 53 95	32 - 25 - 32 mm	46.0	38.0	54.5	31.5	32.0	25	52.0	42.5	146.5	70.0	45	45	35
K- 07 40 53 96	40 - 20 - 40 mm	52.5	31.5	60.0	34.5	40.0	20	63.0	34.5	165.5	66.0	55	55	30
K- 07 40 53 97	40 - 25 - 40 mm	52.5	38.0	60.0	34.5	40.0	25	63.0	42.5	165.5	73.0	55	55	35
K- 07 40 53 98	50 - 20 - 50 mm	63.5	31.5	73.5	41.5	50.0	20	73.0	34.5	201.0	73.0	65	65	30
K- 07 40 53 99	50 - 25 - 50 mm	63.5	38.5	73.5	41.0	50.0	25	73.0	42.5	201.0	80.0	65	65	35
K- 07 40 54 00	50 - 32 - 50 mm	63.5	46.0	73.5	41.0	50.0	32	73.0	52.0	201.0	87.5	65	65	45