

# K-T STECK VB SCHANH IG 20-63 INFI

T-push-in connector Ø 20 mm – Ø 63 mm with integrated gooseneck and internal thread



Darba vides  
Compressed air, vacuum, inert gases  
Eksploatācijas spiediens  
-0,99 bar - 15 bar  
Temperatūras diapazons  
-20 °C to +80 °C  
Blīvgredzens  
NBR  
Blīvējums  
NBR  
Drošības gredzens  
Technopolymer  
Korpuss  
Nickel-plated brass  
Spīlgredzens  
Stainless steel 1.4301  
Uzgrieznis  
Nickel-plated brass

## Produkts

Apzīmējums	Caurules ārējais Ø	Savienojums	A mm	B mm	C mm	E mm	L1 mm	L2 mm	SW mm	SW1 mm
K- 07 40 54 04	20 mm	G 3/8"	11.0	31.5	48.0	34.5	109.0	25.0	28	30
K- 07 40 54 05	20 mm	G 1/2"	13.5	31.5	48.0	34.5	109.0	28.0	28	30
K- 07 40 54 06	25 mm	G 3/8"	11.0	38.5	45.5	42.5	121.5	29.0	35	35
K- 07 40 54 07	25 mm	G 1/2"	13.5	38.5	45.5	42.5	121.5	31.0	35	35
K- 07 40 54 08	32 mm	G 1/2"	13.5	46.0	54.5	52.0	146.5	36.5	45	45
K- 07 40 54 09	40 mm	G 1/2"	13.5	52.5	60.0	63.0	165.5	41.5	55	55
K- 07 40 54 10	50 mm	G 3/4"	14.5	63.5	73.5	73.0	201.0	47.5	65	65