

K-T STECK VB SCHANH IG 20-63 INFI

T-push-in connector Ø 20 mm – Ø 63 mm with integrated gooseneck and internal thread



Darba vides
Compressed air, vacuum, inert gases
Eksploatācijas spiediens
-0,99 bar - 15 bar
Temperatūras diapazons
-20 °C to +80 °C
Blīvgredzens
NBR
Blīvējums
NBR
Drošības gredzens
Technopolymer
Korpuss
Nickel-plated brass
Spīlgredzens
Stainless steel 1.4301
Uzgrieznis
Nickel-plated brass

Produkts

| Apzīmējums | Caurules ārējais Ø | Savienojums | A mm | B mm | C mm | E mm | L1 mm | L2 mm | SW mm | SW1 mm |
|----------------|--------------------|-------------|---------|---------|---------|---------|----------|----------|----------|-----------|
| K- 07 40 54 04 | 20 mm | G 3/8" | 11.0 | 31.5 | 48.0 | 34.5 | 109.0 | 25.0 | 28 | 30 |
| K- 07 40 54 05 | 20 mm | G 1/2" | 13.5 | 31.5 | 48.0 | 34.5 | 109.0 | 28.0 | 28 | 30 |
| K- 07 40 54 06 | 25 mm | G 3/8" | 11.0 | 38.5 | 45.5 | 42.5 | 121.5 | 29.0 | 35 | 35 |
| K- 07 40 54 07 | 25 mm | G 1/2" | 13.5 | 38.5 | 45.5 | 42.5 | 121.5 | 31.0 | 35 | 35 |
| K- 07 40 54 08 | 32 mm | G 1/2" | 13.5 | 46.0 | 54.5 | 52.0 | 146.5 | 36.5 | 45 | 45 |
| K- 07 40 54 09 | 40 mm | G 1/2" | 13.5 | 52.5 | 60.0 | 63.0 | 165.5 | 41.5 | 55 | 55 |
| K- 07 40 54 10 | 50 mm | G 3/4" | 14.5 | 63.5 | 73.5 | 73.0 | 201.0 | 47.5 | 65 | 65 |