

Female connectors, female thread



Ekspluatācijas spiediens
Max. 16 bar (at +20 °C)
Ekspluatācijas temperatūra
-20 °C to +70 °C
Materiāls
Niķelēts misiņš
Blīvgredzens
NBR, siliconefree
Piespiedējgredzens
Hostaform (black nickel-plated for Ø 10, 12)
Spīļžoklis
Stainless steel AISI 316

Apraksts

Economy yet very high-quality series of push-in fittings made of nickel-plated brass. Compact, space-saving, lightweight design. An O-ring in the fillet at the end of the thread guarantees a tight connection for all male thread parts, even on rough surfaces.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	L1 mm	Šļūtenes ārējam Ø	SW
K- 07 40 29 39	G 1/8	26.5	4 mm	9 mm
K- 07 40 29 38	G 1/4	32.0	8 mm	13 mm
K- 07 40 29 36	G 1/4	32.0	10 mm	16 mm
K- 07 40 29 40	G 1/8	27.0	6 mm	11 mm
K- 07 40 29 41	G 1/8	28.0	8 mm	13 mm
K- 07 40 29 37	G 1/4	31.0	6 mm	11 mm