



Ekspluatācijas spiediens
Max. 16 bar (at +20 °C)
Ekspluatācijas temperatūra
-20 °C to +70 °C
Materiāls
Niķelēts misiņš
Blīvgredzens
NBR, siliconefree
Piespiedējgredzens
Hostaform (black nickel-plated for Ø 10, 12)
Spīļžoklis
Stainless steel AISI 316

Apraksts

Economy yet very high-quality series of push-in fittings made of nickel-plated brass. Compact, space-saving, lightweight design. An O-ring in the fillet at the end of the thread guarantees a tight connection for all male thread parts, even on rough surfaces.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	L1 mm	Šļūtenes ārējam Ø	SW
K- 07 40 29 22	M 5	20.5	4 mm	-
K- 07 40 29 23	M 5	22.5	6 mm	-
K- 07 40 29 30	G 1/8	20.0	4 mm	9.0 mm
K- 07 40 29 31	G 1/8	24.0	6 mm	11 mm
K- 07 40 29 32	G 1/8	26.5	8 mm	13 mm
K- 07 40 29 27	G 1/4	21.0	4 mm	9.0 mm
K- 07 40 29 28	G 1/4	24.0	6 mm	11 mm
K- 07 40 29 29	G 1/4	25.0	8 mm	13 mm
K- 07 40 29 26	G 1/4	29.5	10 mm	16 mm
K- 07 40 29 35	G 3/8	25.0	8 mm	13 mm
K- 07 40 29 33	G 3/8	29.5	10 mm	16 mm
K- 07 40 29 34	G 3/8	31.0	12 mm	18 mm
K- 07 40 29 24	G 1/2	30.0	10 mm	16 mm
K- 07 40 29 25	G 1/2	31.0	12 mm	18 mm