


K-SCHOTT-STECKVERB 2

Female bulkhead connectors

HANSA FLEX
OFICIĀLĀ LATVIJAS PĀRSTĀVNICĪBA



Darba spiediens
Max. 16 bar
Eksploatācijas temperatūra
-20 °C to +150 °C
Materiāls
Niķelēts misiņš
Iespilēšanas gredzens
Stainless steel
Piespiedējgredzens
Nickel-plated brass

Apraksts

Push-in fittings, manufactured entirely in nickel-plated brass. All parts with a parallel thread are supplied with an FPM O-ring.
All parts with conical threads are coated with preCOTE 5 dispersion, all fittings in this series can thus also be used at high temperatures (medium compressed air).

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	L1 mm	Šļūtenes ārējais Ø	SW
K- 07 40 27 61	M 10 x 1	31.5	4 mm	13 mm
K- 07 40 27 62	M 14 x 1	33.5	6 mm	17 mm
K- 07 40 27 63	M 16 x 1	37.0	8 mm	18 mm
K- 07 40 27 64	M 17 x 1	39.5	10 mm	20 mm
K- 07 40 47 83	M 20 x 1	42.0	12 mm	24 mm
K- 07 40 47 84	M 22 x 1	46.0	14 mm	25 mm