


# K-STECKVERBINDU 1

Straight push-in connector



Darba spiediens  
Max. 16 bar  
Eksploatācijas temperatūra  
-20 °C to +80 °C  
Materiāls  
Niķelēts misiņš  
Iespilēšanas gredzens  
Stainless steel  
Piespiedējgredzens  
Hostaform

## Apraksts

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	šļūtenes ārējam Ø
K- 07 40 25 18	M 8 x 0.75	18.4	3 mm
K- 07 40 25 19	M 11 x 1	30.6	4 mm
K- 07 40 25 20	M 14 x 1	33.5	5 mm
K- 07 40 25 21	M 13 x 1	33.0	6 mm
K- 07 40 25 22	M 15 x 1	35.7	8 mm
K- 07 40 25 23	M 17 x 1	39.2	10 mm
K- 07 40 25 24	M 20 x 1	39.7	12 mm
K- 07 40 25 25	M 24 x 1	45.9	14 mm