


K-STECKVERBINDU 1

Straight push-in connector



Darba spiediens
Max. 16 bar
Eksploatācijas temperatūra
-20 °C to +80 °C
Materiāls
Niķelēts misiņš
Iespilēšanas gredzens
Stainless steel
Piespiedējgredzens
Hostaform

Apraksts

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Vītnes | L1 mm | šļūtenes ārējam Ø |
|----------------|------------|----------|-------------------|
| K- 07 40 25 18 | M 8 x 0.75 | 18.4 | 3 mm |
| K- 07 40 25 19 | M 11 x 1 | 30.6 | 4 mm |
| K- 07 40 25 20 | M 14 x 1 | 33.5 | 5 mm |
| K- 07 40 25 21 | M 13 x 1 | 33.0 | 6 mm |
| K- 07 40 25 22 | M 15 x 1 | 35.7 | 8 mm |
| K- 07 40 25 23 | M 17 x 1 | 39.2 | 10 mm |
| K- 07 40 25 24 | M 20 x 1 | 39.7 | 12 mm |
| K- 07 40 25 25 | M 24 x 1 | 45.9 | 14 mm |