



Darba spiediens
Max. 16 bar
Eksploatācijas temperatūra
-20 °C to +80 °C
Materiāls
Niķelēts misiņš
Iespilēšanas gredzens
Stainless steel
Piespiedējgredzens
Hostaform

Apraksts

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	L1 mm	Šļūtenes ārējais Ø
K- 07 40 25 26	M 13 x 1	32.7	4 mm / 6 mm
K- 07 40 25 27	M 15 x 1	34.4	4 mm / 8 mm
K- 07 40 25 28	M 15 x 1	35.0	6 mm / 8 mm
K- 07 40 25 29	M 17 x 1	37.5	6 mm / 10 mm
K- 07 40 25 30	M 20 x 1	39.0	6 mm / 12 mm
K- 07 40 25 31	M 17 x 1	37.8	8 mm / 10 mm
K- 07 40 25 32	M 20 x 1	40.1	8 mm / 12 mm
K- 07 40 25 33	M 20 x 1	40.8	10 mm / 12 mm