


K-STECKVERBINDU ST RED 2

Reducers with push-in plug

HANSA FLEX
OFICIĀLĀ LATVIJAS PĀRSTĀVNICĪBA



Darba spiediens
Max. 16 bar
Eksploatācijas temperatūra
-20 °C to +80 °C
Materiāls
Niķelēts misiņš
Iespilēšanas gredzens
Stainless steel
Piespiedējgredzens
Hostaform

Apraksts

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Iespr. nīp. mm	L1 mm	šļūtenes ārējais Ø
K- 07 40 26 16	4	26.0	3 mm
K- 07 40 26 17	6	29.9	4 mm
K- 07 40 26 18	6	36.0	5 mm
K- 07 40 26 19	8	28.7	4 mm
K- 07 40 26 20	8	34.5	5 mm
K- 07 40 26 21	8	31.9	6 mm
K- 07 40 26 22	10	36.2	6 mm
K- 07 40 26 23	10	40.8	8 mm
K- 07 40 26 24	12	40.1	8 mm
K- 07 40 26 25	12	44.3	10 mm
K- 07 40 26 26	14	44.3	10 mm
K- 07 40 26 27	14	50.0	12 mm