

# K-STECKVERSCH AGR OR SK M O

Male connectors, parallel male thread with O-ring and outer hex



Darba spiediens  
Max. 16 bar  
Eksploatācijas temperatūra  
-20 °C to +80 °C  
Materiāls  
Niķelēts misiņš  
Blīvgredzens  
NBR  
Iespilēšanas gredzens  
Stainless steel  
Piespiedējgredzens  
Hostaform

## Apraksts

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	Sešstūra iedobe mm	Šļūtenes ārējais Ø	SW
K- 07 40 24 82	M 3	12.6	1.5	3 mm	Ø 5,8 mm
K- 07 40 24 83	M 5	13.0	2.0	3 mm	Ø 5,8 mm
K- 07 40 24 84	M 5	20.3	2.5	4 mm	Ø 9 mm
K- 07 40 24 85	M 5	22.5	2.5	5 mm	Ø 12 mm
K- 07 40 24 86	M 5	21.9	2.5	6 mm	Ø 11 mm
K- 07 40 24 87	M 7	18.9	3.0	4 mm	Ø 9 mm
K- 07 40 24 88	M 7	23.0	4.0	6 mm	Ø 11 mm
K- 07 40 24 98	G 1/8	18.0	3.0	4 mm	10 mm
K- 07 40 24 99	G 1/8	22.0	3.0	5 mm	13 mm
K- 07 40 25 00	G 1/8	21.6	4.0	6 mm	12 mm
K- 07 40 25 01	G 1/8	25.4	5.0	8 mm	13 mm
K- 07 40 24 94	G 1/4	19.8	3.0	4 mm	10 mm
K- 07 40 24 95	G 1/4	24.0	3.0	5 mm	12 mm
K- 07 40 24 96	G 1/4	20.3	4.0	6 mm	12 mm
K- 07 40 24 97	G 1/4	24.4	6.0	8 mm	14 mm
K- 07 40 24 92	G 1/4	29.2	7.0	10 mm	16 mm
K- 07 40 24 93	G 1/4	30.5	7.0	12 mm	19 mm
K- 07 40 25 05	G 3/8	22.8	6.0	8 mm	14 mm
K- 07 40 25 02	G 3/8	26.5	8.0	10 mm	16 mm
K- 07 40 25 03	G 3/8	28.1	10.0	12 mm	19 mm
K- 07 40 25 04	G 3/8	33.8	10.0	14 mm	22 mm
K- 07 40 24 89	G 1/2	29.8	8.0	10 mm	16 mm
K- 07 40 24 90	G 1/2	29.3	10.0	12 mm	19 mm
K- 07 40 24 91	G 1/2	31.5	12.0	14 mm	22 mm