


# K-STECKVERSCH AGR OR SK M O

## 1

Male connectors, parallel male thread with O-ring and outer hex



Darba spiediens  
Max. 16 bar  
Eksploatācijas temperatūra  
-20 °C to +150 °C  
Materiāls  
Niķelēts misiņš  
Blīvgredzens  
FKM (FPM)  
Iespīlēšanas gredzens  
Stainless steel  
Piespiedējgredzens  
Nickel-plated brass

## Apraksts

Push-in fittings, manufactured entirely in nickel-plated brass. All parts with a parallel thread are supplied with an FPM O-ring.&lt;br&gt;All parts with conical threads are coated with preCOTE 5 dispersion, all fittings in this series can thus also be used at high temperatures (medium compressed air).

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	Šļūtenes ārējam Ø	SW
K- 07 40 27 31	M 5	20.5	4 mm	Ø 9 mm
K- 07 40 27 32	M 5	22.5	6 mm	Ø 10,5 mm
K- 07 40 27 38	G 1/8	20.0	4 mm	9 mm
K- 07 40 27 39	G 1/8	24.0	6 mm	11 mm
K- 07 40 27 40	G 1/8	26.5	8 mm	13 mm
K- 07 40 27 35	G 1/4	21.0	4 mm	9 mm
K- 07 40 47 67	G 1/8	29.0	10 mm	16 mm
K- 07 40 27 36	G 1/4	24.0	6 mm	11 mm
K- 07 40 27 37	G 1/4	25.0	8 mm	13 mm
K- 07 40 27 34	G 1/4	29.0	10 mm	16 mm
K- 07 40 47 66	G 1/4	31.5	12 mm	18 mm
K- 07 40 27 42	G 3/8	25.0	8 mm	13 mm
K- 07 40 27 41	G 3/8	29.5	10 mm	16 mm
K- 07 40 47 68	G 3/8	31.0	12 mm	18 mm
K- 07 40 47 69	G 3/8	34.0	14 mm	21 mm
K- 07 40 27 33	G 1/2	31.0	10 mm	16 mm
K- 07 40 47 64	G 1/2	31.5	12 mm	18 mm
K- 07 40 47 65	G 1/2	34.5	14 mm	21 mm