

# K-STECKVERSCHR AGR-K SK BESCH

**HANSA FLEX**

OFICIĀLĀ LATVIJAS PĀRSTĀVNICĪBA

Male connectors, conical male thread, coated with outer hex



Darba spiediens  
Max. 16 bar  
Eksploatācijas temperatūra  
-20 °C to +150 °C  
Materiāls  
Niķelēts misiņš  
Iespilēšanas gredzens  
Stainless steel  
Piespiedējgredzens  
Nickel-plated brass

## Apraksts

Push-in fittings, manufactured entirely in nickel-plated brass. All parts with a parallel thread are supplied with an FPM O-ring.<br>All parts with conical threads are coated with preCOTE 5 dispersion, all fittings in this series can thus also be used at high temperatures (medium compressed air).

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

| Apzīmējums     | Vītnes | L1<br>mm | Šļūtenes ārējam Ø | SW    |
|----------------|--------|----------|-------------------|-------|
| K- 07 40 27 26 | R 1/8  | 22.5     | 4 mm              | 10 mm |
| K- 07 40 27 27 | R 1/8  | 24.5     | 6 mm              | 11 mm |
| K- 07 40 27 28 | R 1/8  | 27.5     | 8 mm              | 13 mm |
| K- 07 40 47 62 | R 1/4  | 22.5     | 4 mm              | 14 mm |
| K- 07 40 27 24 | R 1/4  | 24.5     | 6 mm              | 14 mm |
| K- 07 40 27 25 | R 1/4  | 27.5     | 8 mm              | 13 mm |
| K- 07 40 27 23 | R 1/4  | 32.5     | 10 mm             | 16 mm |
| K- 07 40 47 61 | R 1/4  | 32.5     | 12 mm             | 17 mm |
| K- 07 40 27 30 | R 3/8  | 28.0     | 8 mm              | 17 mm |
| K- 07 40 27 29 | R 3/8  | 32.5     | 10 mm             | 17 mm |
| K- 07 40 47 63 | R 3/8  | 30.5     | 12 mm             | 17 mm |
| K- 07 40 47 60 | R 1/2  | 33.0     | 12 mm             | 22 mm |