



Darba spiediens
Max. 16 bar
Eksploatācijas temperatūra
-20 °C to +80 °C
Materiāls
Niķelēts misiņš
Iespilēšanas gredzens
Stainless steel
Piespiedējgredzens
Hostaform

Apraksts

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	L1 mm	Šļūtenes ārējam Ø	SW
K- 07 40 25 06	M 5	15.7	3 mm	7 mm
K- 07 40 25 12	G 1/8	26.2	4 mm	10 mm
K- 07 40 25 13	G 1/8	27.5	5 mm	12 mm
K- 07 40 25 14	G 1/8	27.1	6 mm	12 mm
K- 07 40 25 15	G 1/8	28.1	8 mm	13 mm
K- 07 40 25 09	G 1/4	28.6	4 mm	10 mm
K- 07 40 47 15	G 1/4	29.5	5 mm	12 mm
K- 07 40 25 10	G 1/4	29.3	6 mm	12 mm
K- 07 40 25 11	G 1/4	30.0	8 mm	14 mm
K- 07 40 25 08	G 1/4	31.8	10 mm	16 mm
K- 07 40 25 16	G 3/8	36.8	10 mm	16 mm
K- 07 40 25 17	G 3/8	37.0	12 mm	19 mm
K- 07 40 25 07	G 1/2	40.5	12 mm	19 mm