


K-STECKVERSCHR IG SK 1

Male connectors, parallel female thread with outer hex



Darba spiediens
Max. 16 bar
Eksploatācijas temperatūra
-20 °C to +150 °C
Materiāls
Niķelēts misiņš
Iespilēšanas gredzens
Stainless steel
Piespiedējgredzens
Nickel-plated brass

Apraksts

Push-in fittings, manufactured entirely in nickel-plated brass. All parts with a parallel thread are supplied with an FPM O-ring.
All parts with conical threads are coated with preCOTE 5 dispersion, all fittings in this series can thus also be used at high temperatures (medium compressed air).

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	L1 mm	Šļūtenes ārējam Ø	SW
K- 07 40 27 46	G 1/8	26.5	4 mm	9 mm
K- 07 40 27 47	G 1/8	27.0	6 mm	11 mm
K- 07 40 27 48	G 1/8	28.0	8 mm	13 mm
K- 07 40 47 71	G 1/4	29.5	4 mm	9 mm
K- 07 40 27 44	G 1/4	31.0	6 mm	11 mm
K- 07 40 27 45	G 1/4	32.0	8 mm	13 mm
K- 07 40 27 43	G 1/4	32.0	10 mm	16 mm
K- 07 40 47 70	G 1/4	40.0	12 mm	20 mm
K- 07 40 47 72	G 3/8	37.5	10 mm	20 mm
K- 07 40 47 73	G 3/8	39.5	12 mm	20 mm