



Ekspluatācijas temperatūra
Max. 80 °C (with O-ring, NBR)
Spiediens
Max. 60 bar
Materiāls
Niķelēts misiņš

Apraksts

Suitable for air, water, oil, steam, etc.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vitnes	L1 mm	L2 mm	SW	šļūtenei
K- 07 40 13 59	G 1/8	30.0	6.5	14 mm	LW 6 mm
K- 07 40 13 60	G 1/8	31.0	6.0	15 mm	LW 8 mm
K- 07 40 13 61	G 1/8	31.0	6.0	15 mm	LW 9 mm
K- 07 40 13 62	G 1/4	32.0	8.0	17 mm	LW 6 mm
K- 07 40 13 63	G 1/4	33.0	8.0	18 mm	LW 9 mm
K- 07 40 13 64	G 1/4	33.0	8.0	18 mm	LW 12 mm
K- 07 40 49 89	G 1/4	32.0	8.0	17 mm	LW 8 mm
K- 07 40 49 90	G 1/4	33.0	8.0	17 mm	LW 10 mm
K- 07 40 49 96	G 1/4	33.0	8.0	18 mm	LW 13 mm
K- 07 40 49 97	G 3/8	33.0	9.0	20 mm	LW 6 mm
K- 07 40 49 98	G 3/8	33.0	9.0	20 mm	LW 8 mm
K- 07 40 13 65	G 3/8	34.0	9.0	21 mm	LW 9 mm
K- 07 40 49 91	G 3/8	34.0	9.0	20 mm	LW 10 mm
K- 07 40 13 66	G 3/8	34.0	9.0	21 mm	LW 12 mm
K- 07 40 49 92	G 3/8	34.0	9.0	21 mm	LW 13 mm
K- 07 40 13 67	G 1/2	36.0	11.0	26 mm	LW 12 mm
K- 07 40 49 93	G 1/2	36.0	10.0	24 mm	LW 13 mm
K- 07 40 49 94	G 1/2	40.0	10.0	25 mm	LW 16 mm
K- 07 40 49 95	G 1/2	40.0	10.0	24 mm	LW 19 mm