



Ekspluatācijas temperatūra  
Max. 150 °C  
Spiediens  
Max. 60 bar  
Materiāls  
Niķelēts misiņš

## Apraksts

Suitable for air, water, oil, steam, etc.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

| Apzīmējums     | Vitnes | L1<br>mm | L2<br>mm | SW    | šļūtenei |
|----------------|--------|----------|----------|-------|----------|
| K- 07 40 11 76 | G 1/8  | 28.0     | 8.5      | 12 mm | LW 6 mm  |
| K- 07 40 11 77 | G 1/8  | 28.0     | 8.5      | 12 mm | LW 8 mm  |
| K- 07 40 11 78 | G 1/8  | 28.0     | 8.5      | 12 mm | LW 9 mm  |
| K- 07 40 11 79 | G 1/8  | 28.0     | 8.5      | 12 mm | LW 10 mm |
| K- 07 40 11 80 | G 1/4  | 33.0     | 10.0     | 15 mm | LW 6 mm  |
| K- 07 40 11 81 | G 1/4  | 33.0     | 10.0     | 15 mm | LW 8 mm  |
| K- 07 40 11 82 | G 1/4  | 33.0     | 10.0     | 15 mm | LW 9 mm  |
| K- 07 40 11 83 | G 1/4  | 33.0     | 10.0     | 15 mm | LW 10 mm |
| K- 07 40 11 84 | G 1/4  | 33.0     | 10.0     | 15 mm | LW 12 mm |
| K- 07 40 11 85 | G 3/8  | 35.0     | 12.0     | 19 mm | LW 8 mm  |
| K- 07 40 11 86 | G 3/8  | 35.0     | 12.0     | 19 mm | LW 10 mm |
| K- 07 40 11 87 | G 3/8  | 35.0     | 12.0     | 19 mm | LW 12 mm |
| K- 07 40 11 88 | G 3/8  | 35.0     | 12.0     | 19 mm | LW 14 mm |
| K- 07 40 11 89 | G 1/2  | 38.0     | 14.0     | 25 mm | LW 10 mm |
| K- 07 40 11 90 | G 1/2  | 41.0     | 14.0     | 25 mm | LW 12 mm |
| K- 07 40 11 91 | G 1/2  | 41.0     | 14.0     | 25 mm | LW 14 mm |