



Ekspluatācijas temperatūra
Max. 150 °C
Spiediens
Max. 60 bar
Materiāls
Niķelēts misiņš

Apraksts

Suitable for air, water, oil, steam, etc.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītne 1	Vītne 2	L1 mm	L2 mm	L3 mm	SW
K- 07 40 12 80	M 5	M 5	11.5	4.0	4.0	8 mm
K- 07 40 12 81	M 5	G 1/8	14.5	6.0	4.0	14 mm
K- 07 40 12 82	G 1/8	G 1/8	17.0	6.0	6.0	14 mm
K- 07 40 12 83	G 1/8	G 1/4	19.0	8.0	6.0	17 mm
K- 07 40 12 84	G 1/8	G 3/8	20.0	9.0	6.0	20 mm
K- 07 40 12 85	G 1/4	G 1/4	21.0	8.0	8.0	17 mm
K- 07 40 12 86	G 1/4	G 3/8	22.0	9.0	8.0	20 mm
K- 07 40 12 87	G 1/4	G 1/2	24.0	10.0	8.0	25 mm
K- 07 40 12 88	G 3/8	G 3/8	24.0	9.0	9.0	20 mm
K- 07 40 12 89	G 3/8	G 1/2	25.5	10.0	9.0	25 mm
K- 07 40 45 02	G 3/8	G 3/4	27.0	12.0	9.0	27 mm
K- 07 40 12 90	G 1/2	G 1/2	26.5	10.0	10.0	25 mm
K- 07 40 12 91	G 1/2	G 3/4	27.5	11.0	10.0	30 mm
K- 07 40 45 03	G 1/2	G 1	32.5	15.0	10.5	34 mm
K- 07 40 12 93	G 3/4	G 3/4	28.0	11.0	11.0	30 mm
K- 07 40 12 92	G 3/4	G 1	30.0	11.0	12.0	36 mm
K- 07 40 12 94	G 1	G 1	31.0	12.0	12.0	36 mm
K- 07 40 45 04	G 1	G 1 1/4	38.0	16.0	15.0	43 mm
K- 07 40 45 05	G 1	G 1 1/2	38.5	16.0	15.0	50 mm
K- 07 40 45 06	G 1	G 2	42.0	18.0	15.0	60 mm
K- 07 40 45 07	G 1 1/4	G 1 1/4	39.0	16.0	16.0	42 mm
K- 07 40 45 08	G 1 1/4	G 1 1/2	40.0	16.0	16.0	50 mm
K- 07 40 45 09	G 1 1/4	G 2	43.0	18.0	16.0	60 mm
K- 07 40 45 10	G 1 1/2	G 1 1/2	39.5	16.0	16.0	50 mm
K- 07 40 45 11	G 1 1/2	G 2	44.5	18.0	17.5	60 mm
K- 07 40 45 12	G 2	G 2	44.0	17.5	17.5	60 mm
K- 07 40 45 13	G 2	G 2 1/2	54.0	24.0	19.0	77 mm
K- 07 40 45 14	G 2	G 3	50.0	20.0	20.0	89 mm
K- 07 40 45 15	G 2 1/2	G 2 1/2	59.0	24.0	24.0	77 mm
K- 07 40 45 16	G 2 1/2	G 3	52.5	20.0	22.5	89 mm
K- 07 40 45 17	G 3	G 3	60.0	24.5	24.5	89 mm