



Ekspluatācijas temperatūra  
Max. 150 °C  
Spiediens  
Max. 60 bar  
Materiāls  
Niķelēts misiņš

## Apraksts

Suitable for air, water, oil, steam, etc.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītne 1	Vītne 2	L1 mm	L2 mm	L3 mm	SW
K- 07 40 12 60	R 1/8	R 1/8	21.0	8.0	8.0	12 mm
K- 07 40 12 61	R 1/8	R 1/4	24.0	11.0	8.0	14 mm
K- 07 40 12 62	R 1/8	R 3/8	25.0	11.5	8.0	17 mm
K- 07 40 12 63	R 1/4	R 1/4	27.0	11.0	11.0	14 mm
K- 07 40 12 64	R 1/4	R 3/8	28.0	11.5	11.0	17 mm
K- 07 40 12 65	R 1/4	R 1/2	32.0	14.0	11.0	22 mm
K- 07 40 12 66	R 3/8	R 3/8	29.0	11.5	11.5	17 mm
K- 07 40 12 67	R 3/8	R 1/2	32.5	14.0	11.5	22 mm
K- 07 40 12 68	R 1/2	R 1/2	35.0	14.0	14.0	22 mm
K- 07 40 12 69	R 1/2	R 3/4	37.0	16.5	14.0	27 mm
K- 07 40 12 71	R 3/4	R 3/4	40.0	16.5	16.5	27 mm
K- 07 40 12 70	R 3/4	R 1	42.5	19.0	16.5	34 mm
K- 07 40 12 72	R 1	R 1	45.5	19.0	19.0	34 mm