



maks. ekspluatācijas spiediens
60 bar
maks. ekspluatācijas temperatūra
150 °C
Materiāls
Niķelēts misiņš

Apraksts

For air, water, steam, oil, etc.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vitnes	L1 mm	L2 mm	SW	šļūtenei
K- 07 40 14 04	R 1/8	31.5	8.0	12 mm	LW 6 mm
K- 07 40 14 05	R 1/8	31.5	8.0	12 mm	LW 8 mm
K- 07 40 14 06	R 1/8	31.5	8.0	12 mm	LW 9 mm
K- 07 40 14 07	R 1/8	32.5	8.0	12 mm	LW 10 mm
K- 07 40 14 08	R 1/4	35.0	11.0	14 mm	LW 6 mm
K- 07 40 14 09	R 1/4	35.0	11.0	14 mm	LW 8 mm
K- 07 40 14 10	R 1/4	35.0	11.0	14 mm	LW 9 mm
K- 07 40 14 11	R 1/4	36.0	11.0	14 mm	LW 10 mm
K- 07 40 14 12	R 1/4	36.0	11.0	14 mm	LW 12 mm
K- 07 40 14 13	R 3/8	35.5	11.5	17 mm	LW 9 mm
K- 07 40 14 14	R 3/8	36.5	11.5	17 mm	LW 10 mm
K- 07 40 14 15	R 3/8	36.5	11.5	17 mm	LW 12 mm
K- 07 40 14 16	R 1/2	38.5	14.0	22 mm	LW 9 mm
K- 07 40 14 17	R 1/2	39.5	14.0	22 mm	LW 10 mm
K- 07 40 14 18	R 1/2	39.5	14.0	22 mm	LW 12 mm