

K-L-MEHRFACHVERT 2 DR AGR OR CLICK

Multiple union elbows with inner hex, 2 outlets, swivel type, parallel male thread with O-ring



Darba spiediens
Max. 16 bar
Eksploatācijas temperatūra
-20 °C to +80 °C
Materiāls
Niķelēts misiņš
Blīvgredzens
NBR
Iespīlēšanas gredzens
Stainless steel
Piespiedējgredzens
Hostaform

Apraksts

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	Šļūtenes ārējais Ø	SW
K- 07 40 26 50	M 5	30.3	20.2	4 mm	2 mm
K- 07 40 26 51	M 5	30.3	23.5	6 mm	2 mm
K- 07 40 26 55	G 1/8	40.9	20.2	4 mm	3 mm
K- 07 40 47 28	G 1/8	42.0	25.0	5 mm	5 mm
K- 07 40 26 56	G 1/8	40.9	23.5	6 mm	3 mm
K- 07 40 26 57	G 1/8	40.9	24.8	8 mm	3 mm
K- 07 40 26 53	G 1/4	47.0	23.0	6 mm	4 mm
K- 07 40 26 54	G 1/4	47.0	26.5	8 mm	4 mm
K- 07 40 26 52	G 1/4	47.0	31.4	10 mm	4 mm