

# K-L-MEHRFACHVERT 2 DR AGR OR CLICK

Multiple union elbows with inner hex, 2 outlets, swivel type, parallel male thread with O-ring



Darba spiediens  
Max. 16 bar  
Eksploatācijas temperatūra  
-20 °C to +80 °C  
Materiāls  
Niķelēts misiņš  
Blīvgredzens  
NBR  
Iespīlēšanas gredzens  
Stainless steel  
Piespiedējgredzens  
Hostaform

## Apraksts

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

| Apzīmējums     | Vītnes | L1<br>mm | L2<br>mm | Šļūtenes ārējam Ø | SW   |
|----------------|--------|----------|----------|-------------------|------|
| K- 07 40 26 50 | M 5    | 30.3     | 20.2     | 4 mm              | 2 mm |
| K- 07 40 26 51 | M 5    | 30.3     | 23.5     | 6 mm              | 2 mm |
| K- 07 40 26 55 | G 1/8  | 40.9     | 20.2     | 4 mm              | 3 mm |
| K- 07 40 47 28 | G 1/8  | 42.0     | 25.0     | 5 mm              | 5 mm |
| K- 07 40 26 56 | G 1/8  | 40.9     | 23.5     | 6 mm              | 3 mm |
| K- 07 40 26 57 | G 1/8  | 40.9     | 24.8     | 8 mm              | 3 mm |
| K- 07 40 26 53 | G 1/4  | 47.0     | 23.0     | 6 mm              | 4 mm |
| K- 07 40 26 54 | G 1/4  | 47.0     | 26.5     | 8 mm              | 4 mm |
| K- 07 40 26 52 | G 1/4  | 47.0     | 31.4     | 10 mm             | 4 mm |