



Darba spiediens
Max. 16 bar
Eksploatācijas temperatūra
-20 °C to +70°C
Materiāls
Niķelēts misiņš
Iespilēšanas gredzens
Stainless steel
Piespiedējgredzens
Hostaform

Apraksts

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	dobskrūvei	L1 mm	L2 mm	šļūtenes ārējais Ø
K- 07 40 26 82	M 5	18.0	9.0	4 mm
K- 07 40 26 87	G 1/8	20.5	15.0	4 mm
K- 07 40 26 88	G 1/8	23.0	15.0	6 mm
K- 07 40 26 89	G 1/8	24.5	15.0	8 mm
K- 07 40 26 85	G 1/4	24.0	17.0	6 mm
K- 07 40 26 86	G 1/4	26.0	17.0	8 mm
K- 07 40 26 83	G 1/4	27.0	17.0	10 mm
K- 07 40 26 84	G 1/4	28.0	17.0	12 mm
K- 07 40 26 92	G 3/8	27.0	20.0	8 mm
K- 07 40 26 90	G 3/8	28.0	20.0	10 mm
K- 07 40 26 91	G 3/8	29.0	20.0	12 mm