

K-L-STECKVER DREH AG OR

Male elbows, swivel type, parallel male thread with O-ring



Darba spiediens
Max. 16 bar
Eksploatācijas temperatūra
-20 °C to +80 °C
Materiāls
Niķelēts misiņš
Blīvgredzens
NBR
Iespīlēšanas gredzens
Stainless steel
Piespiedējgredzens
Hostaform

Apraksts

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	šļūtenes ārējam Ø	SW
K- 07 40 25 68	M 5	18.6	15.3	4 mm	9 mm
K- 07 40 25 69	M 5	22.8	15.3	5 mm	9 mm
K- 07 40 25 70	M 5	21.9	15.3	6 mm	9 mm
K- 07 40 25 79	G 1/8	18.6	19.1	4 mm	12 mm
K- 07 40 25 80	G 1/8	22.8	19.1	5 mm	12 mm
K- 07 40 25 81	G 1/8	21.9	19.1	6 mm	12 mm
K- 07 40 25 82	G 1/8	25.4	19.1	8 mm	12 mm
K- 07 40 25 75	G 1/4	18.6	21.1	4 mm	14 mm
K- 07 40 25 76	G 1/4	22.8	21.8	5 mm	14 mm
K- 07 40 25 77	G 1/4	21.9	21.1	6 mm	14 mm
K- 07 40 25 78	G 1/4	25.4	21.1	8 mm	14 mm
K- 07 40 25 74	G 1/4	27.2	24.8	10 mm	14 mm
K- 07 40 47 20	G 1/4	30.0	25.6	12 mm	14 mm
K- 07 40 25 85	G 3/8	23.6	27.1	8 mm	17 mm
K- 07 40 25 83	G 3/8	27.2	27.1	10 mm	17 mm
K- 07 40 25 84	G 3/8	30.0	27.1	12 mm	17 mm
K- 07 40 25 71	G 1/2	27.2	30.7	10 mm	22 mm
K- 07 40 25 72	G 1/2	30.0	30.7	12 mm	22 mm
K- 07 40 25 73	G 1/2	33.0	32.3	14 mm	22 mm