

# K-L-STECKVER DREH AG OR 2

Male elbows, swivel type, parallel male thread with O-ring



Darba spiediens  
Max. 16 bar  
Eksploatācijas temperatūra  
-20 °C to +150 °C  
Materiāls  
Niķelēts misiņš  
Blīvgredzens  
FKM (FPM)  
Iespīlēšanas gredzens  
Stainless steel  
Piespiedējgredzens  
Nickel-plated brass

## Apraksts

Push-in fittings, manufactured entirely in nickel-plated brass. All parts with a parallel thread are supplied with an FPM O-ring.<br>All parts with conical threads are coated with preCOTE 5 dispersion, all fittings in this series can thus also be used at high temperatures (medium compressed air).

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	Šļūtenes ārējam Ø	SW
K- 07 40 27 65	M 5	18.0	14.5	4 mm	9 mm
K- 07 40 27 66	M 5	21.0	14.5	6 mm	9 mm
K- 07 40 27 72	G 1/8	20.0	20.0	4 mm	13 mm
K- 07 40 27 73	G 1/8	21.0	20.0	6 mm	13 mm
K- 07 40 27 74	G 1/8	24.0	20.0	8 mm	13 mm
K- 07 40 27 69	G 1/4	20.0	24.0	4 mm	13 mm
K- 07 40 27 70	G 1/4	21.0	24.0	6 mm	13 mm
K- 07 40 27 71	G 1/4	24.0	24.0	8 mm	13 mm
K- 07 40 27 68	G 1/4	27.0	24.0	10 mm	16 mm
K- 07 40 47 86	G 1/4	29.0	30.5	12 mm	16 mm
K- 07 40 27 76	G 3/8	24.0	25.5	8 mm	13 mm
K- 07 40 27 75	G 3/8	27.0	28.0	10 mm	16 mm
K- 07 40 47 85	G 1/2	29.0	33.5	12 mm	20 mm
K- 07 40 27 67	G 1/2	27.0	30.0	10 mm	16 mm
K- 07 40 47 87	G 3/8	29.0	28.5	12 mm	20 mm