

K-L-STECKVER ISK DREH AG OR 1

Banjo elbows with inner hex, swivel type, parallel male thread with O-ring



Darba spiediens
Max. 16 bar
Eksploatācijas temperatūra
-20 °C to +80 °C
Materiāls
Niķelēts misiņš
Blīvgredzens
NBR
Iespīlēšanas gredzens
Stainless steel
Piespiedējgredzens
Hostaform

Apraksts

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	Šļūtenes ārējais Ø	SW
K- 07 40 25 98	M 3	12.2	13.2	3 mm	1,5 mm
K- 07 40 25 99	M 5	12.7	13.7	3 mm	2 mm
K- 07 40 26 00	M 5	20.2	18.4	4 mm	2 mm
K- 07 40 26 01	M 5	24.0	19.0	5 mm	2 mm
K- 07 40 26 02	M 5	23.5	18.4	6 mm	2 mm
K- 07 40 26 03	M 7	20.2	18.5	4 mm	3 mm
K- 07 40 26 04	M 7	23.5	18.5	6 mm	3 mm
K- 07 40 26 09	G 1/8	21.3	24.9	4 mm	3 mm
K- 07 40 26 10	G 1/8	24.8	26.2	5 mm	3 mm
K- 07 40 26 11	G 1/8	23.0	24.9	6 mm	3 mm
K- 07 40 26 12	G 1/8	24.8	24.9	8 mm	3 mm
K- 07 40 26 07	G 1/4	24.5	29.4	6 mm	4 mm
K- 07 40 26 08	G 1/4	26.5	29.4	8 mm	4 mm
K- 07 40 26 06	G 1/4	31.4	29.4	10 mm	4 mm
K- 07 40 47 24	G 1/4	33.0	29.4	12 mm	4 mm
K- 07 40 26 15	G 3/8	28.5	35.6	8 mm	5 mm
K- 07 40 26 13	G 3/8	32.8	35.6	10 mm	5 mm
K- 07 40 26 14	G 3/8	35.3	35.6	12 mm	5 mm
K- 07 40 26 05	G 1/2	37.0	40.8	12 mm	8 mm