

# K-L-STECKVER SK AGR OR

Banjo elbows with outer hex, parallel male thread with O-ring



Darba spiediens  
Max. 16 bar  
Eksploatācijas temperatūra  
-20 °C to +150 °C  
Materiāls  
Niķelēts misiņš  
Blīvgredzens  
FKM (FPM)  
Iespīlēšanas gredzens  
Stainless steel  
Piespiedējgredzens  
Nickel-plated brass

## Apraksts

Push-in fittings, manufactured entirely in nickel-plated brass. All parts with a parallel thread are supplied with an FPM O-ring.<br>All parts with conical threads are coated with preCOTE 5 dispersion, all fittings in this series can thus also be used at high temperatures (medium compressed air).

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	Šļūtenes ārējam Ø	SW
K- 07 40 27 92	M 5	18.0	17.5	4 mm	8 mm
K- 07 40 27 93	M 5	19.0	17.5	5 mm	8 mm
K- 07 40 27 94	M 5	19.5	19.5	6 mm	8 mm
K- 07 40 27 98	G 1/8	20.5	28.0	4 mm	14 mm
K- 07 40 27 99	G 1/8	23.0	28.0	6 mm	14 mm
K- 07 40 28 00	G 1/8	24.5	28.0	8 mm	14 mm
K- 07 40 27 96	G 1/4	24.0	33.0	6 mm	17 mm
K- 07 40 27 97	G 1/4	26.0	33.0	8 mm	17 mm
K- 07 40 27 95	G 1/4	27.0	33.0	10 mm	17 mm
K- 07 40 28 02	G 3/8	27.0	36.0	8 mm	19 mm
K- 07 40 47 94	G 3/8	28.0	36.0	10 mm	19 mm
K- 07 40 28 01	G 3/8	29.0	36.0	12 mm	19 mm
K- 07 40 47 93	G 1/2	34.5	42.0	12 mm	24 mm