


Male branch tees, swivel type, parallel male thread



Ekspluatācijas spiediens  
Max. 16 bar (at +20 °C)  
Ekspluatācijas temperatūra  
-20 °C to +70 °C  
Materiāls  
Niķelēts misiņš  
Blīvgredzens  
NBR, siliconefree  
Piespiedējgredzens  
Hostaform (black nickel-plated for Ø 10, 12)  
Spīļžoklis  
Stainless steel AISI 316

## Apraksts

Economy yet very high-quality series of push-in fittings made of nickel-plated brass. Compact, space-saving, lightweight design. An O-ring in the fillet at the end of the thread guarantees a tight connection for all male thread parts, even on rough surfaces.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	Šļūtenes ārējam Ø	SW
K- 07 40 29 85	G 1/8	35.0	18.5	4 mm	13 mm
K- 07 40 29 86	G 1/8	42.0	18.5	6 mm	13 mm
K- 07 40 29 87	G 1/8	46.0	20.5	8 mm	13 mm
K- 07 40 29 83	G 1/4	42.0	22.5	6 mm	13 mm
K- 07 40 29 84	G 1/4	46.0	22.5	8 mm	13 mm
K- 07 40 29 82	G 1/4	51.0	24.5	10 mm	16 mm