



Darba spiediens
Max. 16 bar
Eksploatācijas temperatūra
-20 °C to +70°C
Materiāls
Niķelēts misiņš
Iespilēšanas gredzens
Stainless steel
Piespiedējgredzens
Hostaform

Apraksts

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	dobskrūvei	L1 mm	L2 mm	šļūtenes ārējais Ø
K- 07 40 26 93	M 5	36.0	9.0	4 mm
K- 07 40 26 97	G 1/8	42.0	15.0	4 mm
K- 07 40 26 98	G 1/8	46.0	15.0	6 mm
K- 07 40 26 99	G 1/8	49.0	15.0	8 mm
K- 07 40 26 95	G 1/4	48.0	17.0	6 mm
K- 07 40 26 96	G 1/4	52.0	17.0	8 mm
K- 07 40 26 94	G 1/4	52.0	17.0	10 mm
K- 07 40 27 02	G 3/8	54.0	20.0	8 mm
K- 07 40 27 00	G 3/8	56.0	20.0	10 mm
K- 07 40 27 01	G 3/8	58.0	20.0	12 mm