


# K-T-STECK VERS DRE AG OR

Male branch tees, swivel type, parallel male thread with O-ring



Darba spiediens  
Max. 16 bar  
Eksploatācijas temperatūra  
-20 °C to +150 °C  
Materiāls  
Niķelēts misiņš  
Blīvgredzens  
FKM (FPM)  
Iespīlēšanas gredzens  
Stainless steel  
Piespiedējgredzens  
Nickel-plated brass

## Apraksts

Push-in fittings, manufactured entirely in nickel-plated brass. All parts with a parallel thread are supplied with an FPM O-ring.<br>All parts with conical threads are coated with preCOTE 5 dispersion, all fittings in this series can thus also be used at high temperatures (medium compressed air).

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	Šļūtenes ārējam Ø	SW
K- 07 40 27 80	G 1/8	40.0	20.0	4 mm	13 mm
K- 07 40 27 81	G 1/8	43.0	20.0	6 mm	13 mm
K- 07 40 27 82	G 1/8	47.0	20.0	8 mm	13 mm
K- 07 40 27 78	G 1/4	43.0	24.0	6 mm	13 mm
K- 07 40 27 79	G 1/4	47.0	24.0	8 mm	13 mm
K- 07 40 27 77	G 1/4	53.0	24.0	10 mm	16 mm
K- 07 40 27 84	G 3/8	47.0	25.5	8 mm	13 mm
K- 07 40 27 83	G 3/8	53.0	28.0	10 mm	16 mm
K- 07 40 47 89	G 3/8	58.0	28.5	12 mm	20 mm
K- 07 40 47 88	G 1/2	58.0	33.5	12 mm	20 mm