

K-T-STECK VERS DRE AG OR 1

Male branch tees, swivel type, parallel male thread with O-ring



Darba spiediens
Max. 16 bar
Eksploatācijas temperatūra
-20 °C to +80 °C
Materiāls
Niķelēts misiņš
Blīvgredzens
NBR
Iespīlēšanas gredzens
Stainless steel
Piespiedējgredzens
Hostaform

Apraksts

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	šļūtenes ārējam Ø	SW
K- 07 40 47 21	M 5	37.2	15.3	4 mm	9 mm
K- 07 40 47 22	M 5	43.8	15.3	6 mm	9 mm
K- 07 40 25 91	G 1/8	37.2	19.1	4 mm	12 mm
K- 07 40 25 92	G 1/8	44.6	19.1	5 mm	12 mm
K- 07 40 25 93	G 1/8	43.8	19.1	6 mm	12 mm
K- 07 40 25 94	G 1/8	50.8	19.1	8 mm	12 mm
K- 07 40 47 23	G 1/4	37.2	21.1	4 mm	14 mm
K- 07 40 25 89	G 1/4	43.8	21.1	6 mm	14 mm
K- 07 40 25 90	G 1/4	50.8	21.1	8 mm	14 mm
K- 07 40 25 88	G 1/4	54.4	21.8	10 mm	14 mm
K- 07 40 25 97	G 3/8	47.2	27.1	8 mm	17 mm
K- 07 40 25 95	G 3/8	54.4	27.1	10 mm	17 mm
K- 07 40 25 96	G 3/8	59.0	27.1	12 mm	17 mm
K- 07 40 25 86	G 1/2	59.0	30.7	12 mm	22 mm
K- 07 40 25 87	G 1/2	66.0	32.3	14 mm	22 mm