

# K-T-STECK VERS DRE AG-K

## BE 1

Male branch tees, swivel type, conical male thread, coated



Darba spiediens  
Max. 16 bar  
Eksploatācijas temperatūra  
-20 °C to +150 °C  
Materiāls  
Niķelēts misiņš  
Iespilēšanas gredzens  
Stainless steel  
Piespiedējgredzens  
Nickel-plated brass

## Apraksts

Push-in fittings, manufactured entirely in nickel-plated brass. All parts with a parallel thread are supplied with an FPM O-ring.<br>All parts with conical threads are coated with preCOTE 5 dispersion, all fittings in this series can thus also be used at high temperatures (medium compressed air).

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	šļūtenes ārējam Ø	SW
K- 07 40 28 18	R 1/8	40.0	20.0	4 mm	13 mm
K- 07 40 28 19	R 1/8	43.0	20.0	6 mm	13 mm
K- 07 40 28 20	R 1/8	47.0	20.0	8 mm	13 mm
K- 07 40 28 16	R 1/4	43.0	25.0	6 mm	14 mm
K- 07 40 28 17	R 1/4	47.0	25.0	8 mm	14 mm
K- 07 40 28 15	R 1/4	53.0	26.0	10 mm	16 mm
K- 07 40 28 21	R 3/8	47.0	28.0	8 mm	18 mm
K- 07 40 48 02	R 3/8	53.0	30.0	10 mm	18 mm
K- 07 40 48 03	R 3/8	58.0	32.5	12 mm	20 mm
K- 07 40 48 01	R 1/2	58.0	35.5	12 mm	22 mm