

K-T-STECK VERS ISK DREH AG OR

Male branch tees with inner hex, swivel type, parallel male thread with O-ring



Darba spiediens
Max. 16 bar
Eksploatācijas temperatūra
-20 °C to +80 °C
Materiāls
Niķelēts misiņš
Blīvgredzens
NBR
Iespīlēšanas gredzens
Stainless steel
Piespiedējgredzens
Hostaform

Apraksts

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	Šļūtenes ārējam Ø	SW
K- 07 40 26 31	M 5	40.4	18.4	4 mm	2 mm
K- 07 40 47 25	M 5	47.6	18.8	5 mm	2 mm
K- 07 40 26 32	M 5	47.0	18.4	6 mm	2 mm
K- 07 40 26 34	M 7	40.4	18.5	4 mm	3 mm
K- 07 40 26 35	M 7	47.0	18.5	6 mm	3 mm
K- 07 40 26 44	G 1/8	42.6	24.9	4 mm	3 mm
K- 07 40 47 27	G 1/8	49.5	27.0	5 mm	3 mm
K- 07 40 26 45	G 1/8	46.0	24.9	6 mm	3 mm
K- 07 40 26 46	G 1/8	49.6	24.9	8 mm	3 mm
K- 07 40 26 42	G 1/4	49.0	29.4	6 mm	4 mm
K- 07 40 26 43	G 1/4	53.0	29.4	8 mm	4 mm
K- 07 40 26 41	G 1/4	62.8	29.4	10 mm	4 mm
K- 07 40 47 26	G 1/4	66.0	29.4	12 mm	4 mm
K- 07 40 26 49	G 3/8	57.0	35.6	8 mm	5 mm
K- 07 40 26 47	G 3/8	65.6	35.6	10 mm	5 mm
K- 07 40 26 48	G 3/8	69.6	35.6	12 mm	5 mm
K- 07 40 26 39	G 1/2	73.0	40.8	12 mm	8 mm