



Darba spiediens
Max. 18 bar
Blīvējums
Buna-N
Materiāls
Niķelēts misiņš

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	L1 mm	SW	šļūtenei
K- 07 40 31 01	G 1/8	26.5	14 mm	6 mm / 4 mm
K- 07 40 31 02	G 1/8	26.5	14 mm	8 mm / 6 mm
K- 07 40 30 99	G 1/4	29.5	17 mm	6 mm / 4 mm
K- 07 40 31 00	G 1/4	29.0	17 mm	8 mm / 6 mm
K- 07 40 30 98	G 1/4	31.0	17 mm	10 mm / 8 mm
K- 07 40 31 05	G 3/8	29.5	20 mm	6 mm / 4 mm
K- 07 40 31 06	G 3/8	33.0	20 mm	8 mm / 6 mm
K- 07 40 31 03	G 3/8	35.0	20 mm	10 mm / 8 mm
K- 07 40 31 04	G 3/8	32.5	20 mm	12 mm / 10 mm
K- 07 40 30 97	G 1/2	33.0	24 mm	8 mm / 6 mm
K- 07 40 30 96	G 1/2	38.0	24 mm	10 mm / 8 mm