



Darba spiediens  
Max. 18 bar  
Blīvējums  
Buna-N  
Materiāls  
Niķelēts misiņš

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	SW	šļūtenei
K- 07 40 42 27	R 1/8	21.5	38.5	8 mm	5 mm / 3 mm
K- 07 40 42 28	R 1/8	22.0	39.0	9 mm	6 mm / 4 mm
K- 07 40 42 29	R 1/8	22.0	39.0	12 mm	8 mm / 6 mm
K- 07 40 32 21	R 1/4	22.0	42.0	9 mm	6 mm / 4 mm
K- 07 40 32 22	R 1/4	22.0	42.0	12 mm	8 mm / 6 mm
K- 07 40 32 20	R 1/4	25.5	41.0	11 mm	10 mm / 8 mm
K- 07 40 42 32	R 3/8	23.0	45.0	12 mm	8 mm / 6 mm
K- 07 40 42 30	R 3/8	25.0	47.0	12 mm	10 mm / 8 mm
K- 07 40 42 31	R 3/8	31.0	55.0	17 mm	12 mm / 10 mm
K- 07 40 42 25	R 1/2	28.5	54.5	17 mm	10 mm / 8 mm
K- 07 40 42 26	R 1/2	31.0	57.0	17 mm	12 mm / 10 mm