



Darba spiediens
Max. 18 bar
Blīvējums
Buna-N
Materiāls
Niķelēts misiņš

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	Sešstūris	SW	Šļūtenei
K- 07 40 31 52	M 5	16.0	17.5	Male	8 mm	5 mm / 3 mm
K- 07 40 31 53	M 5	16.0	17.5	Male	8 mm	6 mm / 4 mm
K- 07 40 31 61	G 1/8	24.0	28.0	Male	14 mm	5 mm / 3 mm
K- 07 40 31 62	G 1/8	24.0	28.0	Male	14 mm	6 mm / 4 mm
K- 07 40 31 63	G 1/8	24.0	28.0	Male	14 mm	8 mm / 6 mm
K- 07 40 31 60	G 1/8	24.0	28.0	Male	14 mm	10 mm / 8 mm
K- 07 40 31 58	G 1/4	26.0	33.0	Male	17 mm	6 mm / 4 mm
K- 07 40 31 59	G 1/4	26.0	33.0	Male	17 mm	8 mm / 6 mm
K- 07 40 31 57	G 1/4	27.5	33.0	Male	17 mm	10 mm / 8 mm
K- 07 40 31 66	G 3/8	26.0	36.0	Male	19 mm	6 mm / 4 mm
K- 07 40 31 67	G 3/8	28.5	37.0	Male	20 mm	8 mm / 6 mm
K- 07 40 31 64	G 3/8	29.0	37.0	Male	20 mm	10 mm / 8 mm
K- 07 40 31 65	G 3/8	31.5	36.0	Female	5 mm	12 mm / 10 mm
K- 07 40 31 56	G 1/2	29.0	42.0	Male	24 mm	8 mm / 6 mm
K- 07 40 31 54	G 1/2	30.5	42.0	Male	27 mm	10 mm / 8 mm
K- 07 40 31 55	G 1/2	33.0	42.0	Female	8 mm	12 mm / 10 mm