

K-W90 AG-K ISO 7-1 4

Male elbows, conical male thread, acc. to ISO 7-1



Darba spiediens
Max. 18 bar
Blīvējums
Buna-N
Materiāls
Niķelēts misiņš

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	SW	šļūtenei
K- 07 40 31 34	R 1/8	24.5	16.0	9 mm	4 mm / 2 mm
K- 07 40 31 35	R 1/8	21.5	17.0	8 mm	5 mm / 3 mm
K- 07 40 31 36	R 1/8	22.0	17.0	9 mm	6 mm / 4 mm
K- 07 40 31 37	R 1/8	22.0	17.0	12 mm	8 mm / 6 mm
K- 07 40 31 33	R 1/8	25.5	18.5	11 mm	10 mm / 8 mm
K- 07 40 31 31	R 1/4	22.0	20.0	9 mm	6 mm / 4 mm
K- 07 40 31 32	R 1/4	22.0	20.0	12 mm	8 mm / 6 mm
K- 07 40 31 30	R 1/4	25.0	21.0	12 mm	10 mm / 8 mm
K- 07 40 31 40	R 3/8	23.5	22.5	11 mm	6 mm / 4 mm
K- 07 40 31 41	R 3/8	23.0	21.5	12 mm	8 mm / 6 mm
K- 07 40 31 38	R 3/8	25.0	21.5	12 mm	10 mm / 8 mm
K- 07 40 31 39	R 3/8	31.0	24.0	14 mm	12 mm / 10 mm
K- 07 40 31 29	R 1/2	23.5	28.0	16 mm	8 mm / 6 mm
K- 07 40 31 27	R 1/2	28.5	26.0	17 mm	10 mm / 8 mm
K- 07 40 31 28	R 1/2	31.0	26.0	17 mm	12 mm / 10 mm