


# K-XVM ZYL 2

Male connectors, parallel male thread



izmantojamās šļūtenes  
PA, PE, PU  
maks. ekspluatācijas spiediens  
18 bar  
Materiāls  
Niķelēts misiņš

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	SW	šļūtenei
K- 07 40 33 54	M 5	21.0	8 mm	5 mm / 3 mm
K- 07 40 33 55	M 5	21.0	8 mm	6 mm / 4 mm
K- 07 40 33 60	G 1/8	23.0	14 mm	5 mm / 3 mm
K- 07 40 33 61	G 1/8	25.5	13 mm	6 mm / 4 mm
K- 07 40 33 62	G 1/8	25.5	14 mm	8 mm / 6 mm
K- 07 40 33 59	G 1/8	27.5	14 mm	10 mm / 8 mm
K- 07 40 33 57	G 1/4	28.0	16 mm	6 mm / 4 mm
K- 07 40 33 58	G 1/4	28.0	16 mm	8 mm / 6 mm
K- 07 40 33 56	G 1/4	29.5	16 mm	10 mm / 8 mm
K- 07 40 33 65	G 3/8	29.0	19 mm	6 mm / 4 mm
K- 07 40 33 66	G 3/8	29.0	19 mm	8 mm / 6 mm
K- 07 40 33 63	G 3/8	30.5	19 mm	10 mm / 8 mm
K- 07 40 33 64	G 3/8	32.0	19 mm	12 mm / 10 mm