



izmantojamās šļūtenes  
PA, PE, PU  
maks. ekspluatācijas spiediens  
18 bar  
Materiāls  
Niķelēts misiņš

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

| Apzīmējums     | Vītnes | L1<br>mm | L2<br>mm | SW    | šļūtenei     |
|----------------|--------|----------|----------|-------|--------------|
| K- 07 40 33 99 | M 5    | 17.0     | 17.5     | 8 mm  | 5 mm / 3 mm  |
| K- 07 40 34 00 | M 5    | 18.0     | 17.5     | 8 mm  | 6 mm / 4 mm  |
| K- 07 40 34 04 | G 1/8  | 24.0     | 28.0     | 14 mm | 6 mm / 4 mm  |
| K- 07 40 34 05 | G 1/8  | 24.0     | 28.0     | 14 mm | 8 mm / 6 mm  |
| K- 07 40 34 02 | G 1/4  | 26.0     | 29.5     | 17 mm | 6 mm / 4 mm  |
| K- 07 40 34 03 | G 1/4  | 26.0     | 29.5     | 17 mm | 8 mm / 6 mm  |
| K- 07 40 34 01 | G 1/4  | 27.5     | 33.0     | 17 mm | 10 mm / 8 mm |
| K- 07 40 34 07 | G 3/8  | 27.5     | 31.5     | 22 mm | 8 mm / 6 mm  |
| K- 07 40 34 06 | G 3/8  | 28.5     | 31.5     | 22 mm | 10 mm / 8 mm |