



Modelis
Uzmavuzgrieznis 10° platgala savienojumam
Materiāls
Tērauds
Virsmas aizsardzība
galvaniskais pārklājums

Produkts

Apzīmējums	Sērija	Ekspluatācijas spiediens bar	Ø d2 mm	G1	L1 mm	SW mm
UEM NW 04 LB V	L	PN 315	6	M 12 x 1,5	17.8	14
UEM NW 06 LB V	L	PN 315	8	M 14 x 1.5	17.8	17
UEM NW 08 LB V	L	PN 315	10	M 16 x 1.5	18.8	19
UEM NW 10 LB V	L	PN 315	12	M 18 x 1,5	18.8	22
UEM NW 13 LB V	L	PN 315	15	M 22 x 1.5	20.3	27
UEM NW 16 LB V	L	PN 315	18	M 26 x 1,5	21.3	32
UEM NW 20 LB V	L	PN 160	22	M 30 x 2	24.0	36
UEM NW 25 LB V	L	PN 160	28	M 36 x 2	25.0	41
UEM NW 32 LB V	L	PN 160	35	M 45 x 2	28.0	50
UEM NW 40 LB V	L	PN 160	42	M 52 x 2	28.0	60
UEM NW 04 SB V	S	PN 630	8	M 16 x 1.5	20.0	22
UEM NW 06 SB V	S	PN 630	10	M 18 x 1,5	21.5	24
UEM NW 08 SB V	S	PN 630	12	M 20 x 1.5	21.5	27
UEM NW 10 SB V	S	PN 630	14	M 22 x 1.5	26.0	30
UEM NW 13 SB V	S	PN 400	16	M 24 x 1.5	26.0	30
UEM NW 16 SB V	S	PN 400	20	M 30 x 2	30.5	36
UEM NW 20 SB V	S	PN 400	25	M 36 x 2	38.0	46
UEM NW 25 SB V	S	PN 400	30	M 42 x 2	39.0	50
UEM NW 32 SB V	S	PN 315	38	M 52 x 2	46.0	60

Sērija: LL = ļoti vieglā L = vieglā S = smagā

PN = nominālais spiediens PB = maks. ekspluatācijas spiediens

Ø d2 = caurules ārējais diametrs