



Spiediena diapazons
Max. 60 bar
Temperatūra
Max. 150 °C
Materiāls
Niķelēts misiņš

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Caurules ārējais Ø	Vītnes	L1 mm	SW	SW1 mm
K- 07 40 20 36	4 mm	G 1/8	24.5	14 mm	10
K- 07 40 20 37	6 mm	G 1/8	25.5	14 mm	12
K- 07 40 20 38	8 mm	G 1/8	26.5	14 mm	14
K- 07 40 20 39	6 mm	G 1/4	30.0	17 mm	12
K- 07 40 20 40	8 mm	G 1/4	31.0	17 mm	14
K- 07 40 20 41	10 mm	G 1/4	35.5	17 mm	19
K- 07 40 20 42	8 mm	G 3/8	31.0	20 mm	14
K- 07 40 20 43	10 mm	G 3/8	36.5	20 mm	19
K- 07 40 20 44	12 mm	G 3/8	36.0	20 mm	22
K- 07 40 20 45	12 mm	G 1/2	39.5	24 mm	22
K- 07 40 20 46	15 mm	G 1/2	40.0	24 mm	27
K- 07 40 20 47	18 mm	G 1/2	42.0	26 mm	32