



Savienojums 1
Savienojuma spraudnis
Savienojums 2
BSP ārējās vītnes, cilindriskas
Materiāls
Tērauds
Virsmas aizsardzība
Hot dip galvanised

Produkts

Apzīmējums	Ekspluatācijas spiediens bar	Savienojuma izmērs mm	G1
PRT S 50 HR 1.1/2	25.0	50	G 1.1/2" -11
PRT S 50 HR 2	25.0	50	G 2" -11
PRT S 70 HR 2	25.0	70	G 2" -11
PRT S 70 HR 2.1/2	25.0	70	G 2.1/2" -11
PRT S 70 HR 3	25.0	70	G 3" -11
PRT S 89 HR 2.1/2	25.0	89	G 2.1/2" -11
PRT S 89 HR 3	25.0	89	G 3" -11
PRT S 108 HR 2.1/2	25.0	108	G 2.1/2" -11
PRT S 108 HR 3	25.0	108	G 3" -11
PRT S 108 HR 4	25.0	108	G 4" -11
PRT S 133 HR 2.1/2	25.0	133	G 2.1/2" -11
PRT S 133 HR 4	25.0	133	G 4" -11
PRT S 133 HR 5	25.0	133	G 5" -11
PRT S 159 HR 2.1/2	25.0	159	G 2.1/2" -11
PRT S 159 HR 4	25.0	159	G 4" -11
PRT S 159 HR 6	25.0	159	G 6" -11