



#### Izmantošana

Air, gases, oils, greases, fuels, organic and inorganic substances

Ekspluatācijas temperatūra

-40 °C to +100 °C

## Apraksts

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

| Apzīmējums     | Ø šļūtenei iekšpusē<br>mm | Ø šļūtenei ārpusē<br>mm | Tinumi | Ø spirālei ārpusē<br>mm | Max. working pressure resistance at 23°C<br>bar | maks. darba ga<br>m |
|----------------|---------------------------|-------------------------|--------|-------------------------|---|---------------------|
| K- 07 10 07 51 | 3.1                       | 4.7                     | 144    | 38                      | 22  | 10.0                |
| K- 07 10 07 52 | 4.8                       | 6.3                     | 140    | 75                      | 16  | 22.5                |
| K- 07 10 07 53 | 6.3                       | 7.9                     | 135    | 75                      | 13  | 22.5                |
| K- 07 10 07 49 | 7.9                       | 9.5                     | 90     | 115                     | 12  | 22.5                |
| K- 07 10 07 50 | 9.5                       | 11.8                    | 70     | 140                     | 11  | 22.5                |