

K-SPIR SCHL B DREH VERSCHRAU

Spiral hose, with swivel adapter fitted at both ends and kink protector



Izmantošana
Air, gases, oils, greases, fuels, organic and inorganic substances
Eksploatācijas temperatūra
-40 °C to +100 °C
Pieslēguma veids
connection nipples and coupling NW 7,2

Apraksts

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Ø šļūtenei iekšpusē mm	Ø šļūtenei ārpusē mm	Tinumi	Vītnes	Ø spirālei ārpusē mm	Max. working pressure resistance at 23°C bar	maks. garu m
K- 07 10 07 34	3.1	4.7	36	R 1/8	38	22	2.5
K- 07 10 07 35	3.1	4.7	72	R 1/8	38	22	5.0
K- 07 10 07 36	3.1	4.7	108	R 1/8	38	22	7.5
K- 07 10 07 37	4.8	6.3	15	R 1/4	75	16	2.5
K- 07 10 07 38	4.8	6.3	30	R 1/4	75	16	5.0
K- 07 10 07 39	4.8	6.3	45	R 1/4	75	16	7.5
K- 07 10 07 40	6.3	7.9	15	R 1/4	75	13	2.5
K- 07 10 07 41	6.3	7.9	30	R 1/4	75	13	5.0
K- 07 10 07 42	6.3	7.9	45	R 1/4	75	13	7.5
K- 07 10 07 28	7.9	9.5	10	R 1/4	115	12	2.5
K- 07 10 07 29	7.9	9.5	20	R 1/4	115	12	5.0
K- 07 10 07 30	7.9	9.5	30	R 1/4	115	12	7.5
K- 07 10 07 31	9.5	11.8	8	R 3/8	140	11	2.5
K- 07 10 07 32	9.5	11.8	15	R 3/8	140	11	5.0
K- 07 10 07 33	9.5	11.8	23	R 3/8	140	11	7.5