

# K-SPIR SCHL DREH VERSCHRAU

## V

Spiral hose, with swivel adapter and kink protector, braided



Ekspluatācijas temperatūra  
-40 °C to +74 °C  
Pieslēguma veids  
with kink protector, swivel type

## Apraksts

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	Ø šļūtenei iekšpusē mm	Ø šļūtenei ārpusē mm	Ø ārējam tinumam mm	Max. working pressure resistance at 23°C bar	maks. darba garums m
K- 07 10 07 43	G 1/4	6.3	9.5	42	14	3.0
K- 07 10 07 44	G 1/4	6.3	9.5	42	14	6.0
K- 07 10 07 45	G 1/4	6.3	9.5	42	14	7.5
K- 07 10 07 46	G 3/8	8.0	12.0	55	14	3.0
K- 07 10 07 47	G 3/8	8.0	12.0	55	14	6.0
K- 07 10 07 48	G 3/8	8.0	12.0	55	14	7.5